

Stainless steel barb locking PA 6.6 cable tie 186 x 4.8 mm transparent (x 100)



Characteristics

- Color : **Transparent**
- Length (mm) : **186**
- Width (mm) : **4.8**
- Thickness (mm) : **1.5**
- Maximum clamping Ø (mm) : **45**
- Traction strength (N) : **220**
- Quantity per box : **100**

Benefits

- No resistance on tightening.
- High level of abrasion resistance.
- Halogen-free.
- UV-resistant.

Compliance marks



GENERAL INFORMATION

Technical details

Pull-tie material: polyamide 6.6.  
 Raw material flammability: UL94V-2.  
 Barb material: stainless steel 304.  
 Installation temperature: - 40 to +60 °C.  
 Operating temperature: -40 to +85 °C.

Application(s)

These cable ties are designed for interior and exterior fixing applications. Perfect for environments where vibration is present, the metal barb ensures regular high performance levels and long-term reliability.

LOGISTIC INFORMATION

Packaging



Basic plastic bag

Height (cm) : 1  
 Length (cm) : 29  
 Depth (cm) : 15  
 Net weight (kg) : 0.147  
 Gross weight (kg) : 0.149



Outer package 1



Carton box

Height (cm) : 46  
 Length (cm) : 36  
 Depth (cm) : 27  
 Net weight (kg) : 22.4  
 Gross weight (kg) : 23.4

x 150



Outer package 2



Pallet

Height (cm) : 118  
 Length (cm) : 120  
 Depth (cm) : 80  
 Net weight (kg) : 468  
 Gross weight (kg) : 488

x 3000

