

Din Rail Perf Sym 35 x 15 2 m



Characteristics

Type : *Perforated symmetrical*

Length : 2

Width : 35

Height : 15

Thickness : 1.5

GENERAL INFORMATION

■ Technical details

Salt spray resistance: 96 hours minimum.

■ Application(s)

1- ASSYMETRIC RAILS:

For the click or screw fixing of terminal blocks or devices with the aid of accessories.

2- SYMETRIC RAILS:

For the click fixing of any modular device without accessories (terminals, circuit breakers, etc.).

Height 7.5 mm: used for fixing lightweight devices (domestic, offices, industry).

Height 15 mm: used for fixing heavier devices and/or when there are greater distances between attachment points.

ADDITIONAL INFORMATION

Material: steel.



Treatment: white zinc plating.

 LOGISTIC INFORMATION

 Packaging



Plastic film



Height (cm) : 15
 Length (cm) : 200
 Depth (cm) : 3.5
 Net weight (kg) : 1.23
 Gross weight (kg) : 1.23



 Outer package 1



Bunch

Height (cm) : 8.5
 Length (cm) : 200
 Depth (cm) : 4
 Net weight (kg) : 12.3
 Gross weight (kg) : 12.3





x 10

 Outer package 2



Pallet

Height (cm) : 31
 Length (cm) : 205
 Depth (cm) : 43
 Net weight (kg) : 310
 Gross weight (kg) : 315



x 250