

Stainless steel barb locking PA 6.6 cable tie 361 x 4.8 mm UV black (x 1000)



Characteristics

- Color : **Black**
- Length (mm) : **361**
- Width (mm) : **4.8**
- Thickness (mm) : **1.5**
- Maximum clamping Ø (mm) : **100**
- Traction strength (N) : **220**
- Quantity per box : **1000**

Benefits

- No resistance on tightening.
- High level of abrasion resistance.
- Halogen-free.
- UV-resistant.

Compliance marks



GENERAL INFORMATION

Technical details

Pull-tie material: polyamide 6.6.
 Raw material flammability: UL94V-2.
 Barb material: stainless steel 304.
 Installation temperature: - 40 to +60 °C.
 Operating temperature: -40 to +85 °C.

Application(s)

These cable ties are designed for interior and exterior fixing applications. Perfect for environments where vibration is present, the metal barb ensures regular high performance levels and long-term reliability.

LOGISTIC INFORMATION

Packaging



Basic plastic bag

Height (cm) : 1
 Length (cm) : 54
 Depth (cm) : 38
 Net weight (kg) : 2.698
 Gross weight (kg) : 2.7



Outer package 1



Carton box

Height (cm) : 46
 Length (cm) : 36
 Depth (cm) : 27
 Net weight (kg) : 8.1
 Gross weight (kg) : 9



Outer package 2



Pallet

Height (cm) : 118
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 180
 Gross weight (kg) : 200

