



Low Smoke Zero Halogen - Flat TPS Cables
LSZH 450/750V 2 Core & 3 Core flat.

Application: For light to medium industrial use. For festoon systems and other applications. Suitable for all building internal wiring applications.

Standard: AS/NZS 5000.2

Conductor: Plain annealed copper (AS/NZS 1125)

Insulation: 90°C LSZH

Core Colour:

2 Core:Red,Black

2 Core Type A:Red,White

3 Core:Red,Green&Yellow,Black



Sheath: 90°C LSZH

Sheath Colour:Light Blue Or Light Orange

Packing Length: 100m, 500m

Normal Operating Temperature: 90°C

Typical Features:

Electra Cables Part No.	Stranding No./mm	Conductor area mm ²	Insulation Thickness mm	Sheath Thickness mm	Nom. O/D mm	Approx. Mass kg/100m
2 Core Twin or Twin Active (No Earth)						
SRF2015VLS	7/0.50	1.5	0.6	0.9	7.2×4.6	6.2
SRF2015AVLS	7/0.50	1.5	0.6	0.9	7.2×4.6	6.2
SRF2025VLS	7/0.67	2.5	0.7	1.0	8.9×5.5	9.6
SRF2025AVLS	7/0.67	2.5	0.7	1.0	8.9×5.5	9.6
SRF2040VLS	7/0.85	4.0	0.8	1.1	10.6×6.5	14.3
SRF2060VLS	7/1.04	6.0	0.8	1.1	11.7×7.0	18.6
3 Core(2 Core +Earth)						
SRF3015VLS	7/0.50	1.5	0.6	0.9	9.8×4.5	8.7
SRF3025VLS	7/0.67	2.5	0.7	1.0	12.4×5.5	13.8
SRF3040VLS	7/0.85 7/0.67(E)	4.0 2.5(E)	0.8 0.7(E)	1.1	14.0×6.4	18.9
SRF3060VLS	7/1.04 7/0.67(E)	6.0 2.5(E)	0.8 0.7(E)	1.1	15.0×6.9	23.6



Quality ISO 9001
 Certified System

Note: Other types or other lengths of the above cables can be manufactured according to customers' specifications.